

araid[®] M500T/5000T

Non-Stop RAID 1 Controller

FIRST

Supports enterprise-level management through SNMP.

- Wide OS compatibility: Windows 11/10/7/XP, Linux, Ubuntu, etc.
- Intuitive display of operation & ARAID status through LCD/LED/Buzzer.
- Cooling fan for additional heat dissipation.
- Supports HDD with capacity up to 18TB.
- Online & offline backup

Back up operating system, programs, and data while in use.

Instantly restore system and data upon drive failure, data corruption or ransomware attack



Use with Different PC Types



Applications



Semiconductor.



Infrastructure.



Manufacturing.



Gaming.



Any applications in which uptime is vital.

Never let a failed drive stop your systems again.

Pri HDD : OK
Sec HDD : OK
Two good drives

Pri HDD : OK
Sec HDD : Fail
One drive failed

Pri HDD : OK
Sec HDD : OFF
Remove failed drive

Rebuilding...
Pri → Sec 02%
Insert new drive
& start disk rebuilding

Rebuilding...
Pri → Sec 02%
↓
Rebuilding...
Pri → Sec 20%
Rebuilding in progress (20%)

Pri HDD :
Sec HDD :
Rebuilding complete



araid[®] M500T/5000T

SATA



	M500T	5000T
Host Interface	SATA III (6.0 Gbps), compatible with SATA I (1.5 Gbps) and SATA II (3.0 Gbps)	
Disk Drive Interface	SATA III (6.0 Gbps) x 2	
RAID Levels	RAID 1, RAID 0 (can be set by the user)	
LCD	Displays ARAID and disk drive status: Cooling fan alert, temperature alert, rebuilding progress, and drive failure	
LED Indicators	Disk drive read and write status	
Disk Drive Failure Alerts	LCD, LED, buzzer, email, and SNMP trap notifications	
Single/Dual Switch	Mirror-on-Demand function (allows manual disk rebuilding). Protects data in the secondary disk from accidental deletion and viruses.	
Cooling Fan	4 cm silent cooling fan	6 cm silent cooling fan
Drivers	None required	
Disk Hot-Swapping	Supported	
Supported OS	Windows (11/10/7/XP), Linux, Mac, Solaris, SCO Unix, NetWare, DOS, etc.	
Operating Temperature	0 °C - 65 °C	
Dimensions	183 mm (W) x 100 mm (H) x 180 mm (D) 7.2 in (W) x 3.9 in (H) x 7.1 in (D)	183 mm (W) x 156 mm (H) x 240 mm (D) 7.2 in (W) x 6.1 in (H) x 9.4 in (D)
Weight (without disk drive)	approx. 1.8 kgs / 4.0 lbs	approx. 2.7 kgs / 6.0 lbs
Power Consumption (without disk drive)	approx. 5.14W ~ 7.32W (depend on models)	
Power Supply	AC 100V~240V	

* Models for IDE and SCSI host interface also available.



ACCORDANCE

10F., No. 258, Nanyang St., Xizhi Dist.,
New Taipei City 221, Taiwan R.O.C.
Tel: +886-2-2726-3239 Fax: +886-2-2728-1322
www.accordance.com.tw
E-mail: sales@accordance.com.tw

151-4-3A Wisma Mutiara Puchong
6 ½ Miles Jalan Puchong
58200 Kuala Lumpur, Malaysia
Tel: 03-77818411
E-mail: araid@accordance.com.my